



## RESISTIVE LOAD BANK 48V with 32A & 80A Constant Discharge

We have attained a matchless position in the marketplace as a manufacturer and supplier of Load Bank. These are highly appreciated by our clients for their use in Power supply equipment, Standard generator testing, Battery discharge, Elevator, Frequency converters, UPS power, and more. The offered banks are used testing of DC or AC supplies with complete accuracy. Their electricity hazard protected mechanism is completely safe to operate. Moreover, our Load Bank has a weather resistant body and has extended operational life.



\*The above shown image is only for representation purpose

### FEATURES:

- ☺ Non-Corrosive Property
- ☺ Stable & Reliable Functioning
- ☺ High Load Storage Capacity

Contact :

### RETRACK SYSTEMS

# 1038, 'HOMBELAKU', 11th Main,  
Hampinagar, Vijayanagar 2nd Stage,  
Bangalore – 560040

**Mob. 9844759090 / 9886359090**

Email : [sales@retracksystems.com](mailto:sales@retracksystems.com) /  
[retracksystems@gmail.com](mailto:retracksystems@gmail.com)  
[www.retracksystems.com](http://www.retracksystems.com)

TECHNICAL SPECIFICATION	
Voltage:	48V DC
Current:	32A / 80A DC

INDICATION
Digital Voltmeter and Current Meter
LED Indicator for Voltage Selection
DISPLAY
Battery Voltage, Discharge Current, AH Discharged, Running Time
SWITCH
Suitable Selector Switch

FEATURES	
Cooling :	Forced Air, using FAN
Protection :	HV Battery Pack Under voltage
Enclosure:	The Load Bank will be Constructed with rugged M.S. Sheets/Mesh
Cables :	One positive and one negative with Ring Terminal (13 mm hole). One set extension cable with Ring Terminal (10-11 mm hole)
Painting:	Powder Coating (Black)
Auxiliary Supply:	230V AC With suitable 3pin socket on door for connecting Aux, AC Supply for cooling fans
Mobility:	Freely movable through suitable wheels
Approximate Dimension:	300 mm x 350 mm x 700 mm (Width x Depth x Height)
RUGGED AND AESTHETIC MECHANICAL AND ELECTRICAL DESIGN	